

System "Low-profile warm water underfloor heating"

For the retroactive fitting of a warm water underfloor heating system



Brief description:

This system makes it quick and easy to retrofit a low-profile warm water underfloor heating system. Thanks to perfectly harmonized products, the installation can be accomplished easily and does not call for any complex conversion work with long drying times.

System benefits:

- Energy savings as a result of low flow temperature and quick regulation of temperature
- Sustainable and economical due to preservation of the building fabric
- Low installation height

Worksteps	Products
Bonding agent	<p>1 R 766 Multi-purpose primer for absorbent and impervious substrates Retrofitted installation of _ low-profile warm water underfloor heating system</p>
Floor leveler	<p>2 DS 40 Thick-layer levelling compound for producing layers of 3 - 40 mm thickness in one application</p>
Flooring adhesive	<p>3 P 680 ELAST STRONG Hard-elastic adhesive for bonding solid and engineered wood flooring</p>
Supplementary product	<p>4 TRD 5 Self-adhesive edge insulation strip for preventing sound transmission</p>

PCI Augsburg GmbH
Piccardstraße 11, 86159 Augsburg,
Tel.: +49 821 5901 0

thomsit-info@pci-group.eu
www.thomsit.com

The above information, in particular recommendations for the handling and use of our products, is based on our professional knowledge and experience. As materials and conditions may vary with each intended application and thus are beyond our sphere of influence, we strongly recommend that in each case sufficient tests are conducted to check the suitability of our products for the intended application method and use. Legal liability cannot be accepted on the basis of the contents of this technical data sheet or any verbal advice given unless there is evidence of wilful intent or gross negligence on our part. This technical data sheet supersedes all previous editions relevant to this product.