


# System "Milled screed underfloor heating"

For the retroactive fitting of a milled screed underfloor heating



**Brief description:**

This system makes it easy and reliable to retrofit a milled screed underfloor heating system. Thanks to perfectly harmonized products, the installation can be accomplished easily and does not call for any complex conversion work with long drying times.

**System benefits:**

- Energy and cost savings as a result of low flow temperature
- Sustainable and economical due to preservation of the building fabric
- Very low installation height

Worksteps	Products
<b>Bonding agent</b>	1 R 790 Filling primer for renovating old flooring with a high number of joints, for securing metal brackets (on load-bearing existing screed, with underfloor heating installed in retroactively milled grooves)
<b>Floor leveler</b>	2 XXL POWER Premium leveling compound for leveling up to 20 mm in one single application
<b>Flooring adhesive</b>	3 T 410 AQUATAACK carpet adhesive for textile coverings on walls and floors
<b>Supplementary product</b>	4 TRD 5 Self-adhesive edge insulation strip for preventing sound transmission

**PCI Augsburg GmbH**  
Piccardstraße 11, 86159 Augsburg,  
Tel.: +49 821 5901 0

thomsit-info@pci-group.eu  
www.thomsit.com

The above information, in particular recommendations for the handling and use of our products, is based on our professional knowledge and experience. As materials and conditions may vary with each intended application and thus are beyond our sphere of influence, we strongly recommend that in each case sufficient tests are conducted to check the suitability of our products for the intended application method and use. Legal liability cannot be accepted on the basis of the contents of this technical data sheet or any verbal advice given unless there is evidence of wilful intent or gross negligence on our part. This technical data sheet supersedes all previous editions relevant to this product.