

System "Parquetry on moist substrates"

For reliable parquetry laying on substrates with residual moisture



Brief description:

With this system and the perfectly harmonized THOMSIT products, you can also lay parquetry on substrates with residual moisture.

System benefits:

- Easy and reliable processing
- Time and cost saving
- Very low-emission products

Worksteps	Products
Substrate repair	<p>1 RS 100 Renovation leveling compound for leveling from 0 - 100 mm in one application</p> <p>R 729 Silicate casting resin for power-bond filling of fine cracks and joints in screed</p>
Primer	<p>2 R 745 Dispersion-based barrier primer for unheated and heated cement screeds with a moisture content up to 3 CM %</p>
Flooring adhesive	<p>3 P 680 ELAST STRONG Hard-elastic adhesive for bonding solid and engineered wood flooring</p>

PCI Augsburg GmbH
Piccardstraße 11, 86159 Augsburg,
Tel.: +49 821 5901 0

thomsit-info@pci-group.eu
www.thomsit.com

The above information, in particular recommendations for the handling and use of our products, is based on our professional knowledge and experience. As materials and conditions may vary with each intended application and thus are beyond our sphere of influence, we strongly recommend that in each case sufficient tests are conducted to check the suitability of our products for the intended application method and use. Legal liability cannot be accepted on the basis of the contents of this technical data sheet or any verbal advice given unless there is evidence of wilful intent or gross negligence on our part. This technical data sheet supersedes all previous editions relevant to this product.